

PRODUCT SPECIFICATIONS :

STANFORD 9 | STANFORD 9+ | STANFORD 12 | STANFORD 12+ | HARMONY I | HARMONY III

STANFORD 9	STANFORD 9+	STANFORD 12	STANFORD 12+	HARMONY I	HARMONY III

TECHNICAL DATA :

	STANFORD 9	STANFORD 9+	STANFORD 12	STANFORD 12+	HARMONY I	HARMONY III
Min.-max. heat output	2 - 12 kW	2 - 12 kW	3 - 14 kW	3 - 14 kW	2 - 12 kW	3 - 14 kW
Heat output to EN13240	9 kW	9 kW	12 kW	12 kW	9 kW	12 kW
Heats up to	360 m ³	360 m ³	420 m ³	420 m ³	360 m ³	420 m ³
Efficiency	76%	76%	76%	76%	76%	76%
CO emissions	0,06%	0,06%	0,09%	0,09%	%	%
Flue diameter	int. 130 / ext. 150 mm.	int. 130 / ext. 150 mm.	int. 150 / ext. 180 mm.	int. 150 / ext. 180 mm.	int. 130 / ext. 150 mm.	int. 150 / ext. 180 mm.
Maximum log length	400 mm.	400 mm.	500 mm.	500 mm.	400 mm.	500 mm.
Weight	150 kg.	170 kg.	200 kg.	240 kg.	150 kg.	200 kg.
Certification	EN 13240	EN 13240	EN 13240	EN 13240	EN 13240	EN 13240

STANDARD FEATURES :

- Multifuel combustion technology
- Cast iron body
- Cast iron firebox protection
- Side loading door
- Top and rear flue exit (Stanford "+" rear exit only)
- Thermostatic primary air control, manual secondary air control
- Self-cleaning ceramic glass
- Ash pan