



UK: Declaration of Performance (DOP)

Aura 1, Aura 11, Aura 2, Aura 3, Aura 3 stone

Product type		Fritstående ovn	
Type, batch or serial number		Aura, 1, Aura 11, Aura 2, Aura 3, Aura 3 stone	
Intended use of the product		This stove is designed for solid fuel and intermittent burning. Without hot water supply.	
Name and Address of the manufacturer		Varde Ovne A/S Pottemagervej 1 7100 Vejle, Danmark	
AVCP		System 3	
Approval place		RRF, Im Lipperfeld 34b, D-46047 Oberhausen	
Notified body no.		NB-No 1625	
Test report no.		Rapport nr. RRF- 40 15 4088, RRF-AU 14 3657 Rapport nr. RRF- 40 17 4484, RRF NS 16 4227	
Declared performance			
Harmonized technical specification		EN 13240:2001/A2:2004/AC:2007 Art. 15a B-VG, NS-3058	
Seasonal Space Efficiency (EEI) EU 2015/1186		108	
Essential characteristics		Performance	
Fire safety			
Reaction to fire		A1	
Distance to combustible materials Minimum distances, in mm		Rear = 125 Sides = 300 Front = 800	
Fuel types		Primary: Wood, moisture content ≤ 25% Secondary: Pressed wood briquettes, moisture content ≤ 12% Air regulation: Manuel stepless	
Emission of combustion products CO OGC Dust NOX	Art 15-A 642 mg/MJ 41 mg/MJ 12 mg/MJ 79 mg/MJ	EN 13240 13% O2 1250 mg/Nm3 – 0,10 % 97 mg/Nm3 21 mg/Nm3 111 mg/Nm3	NS 3058 / NS 3059 Total 3,16 g/kg – max. 3,69 g/kg
Surface temperature		OK	
Electrical safety		–	
Clean ability		OK	
Maximum water operating pressure		–	
Flue gas temperature at nominal heat output		265°C	
Mechanical resistance (to carry a chimney/flue)		OK	
Thermal output			
Normal heat output		5,0 kW	
Room heating output		5,02 kW	
Water heating output		–	
Energy efficiency	81%	81%	
Annual efficiency	72,9 %	72,9 %	

Date of issue: August 31, 2015.
 Udført af: Annette Blendstrup
 Godkendt af: Michael Verman
 Dato/revision: 16.02.2022 / 9

Signed on behalf of the manufacturer

Michael Verman, CEO

